


TLR1690-75W

Linear light of 1690mm with 75W led plate for surface

Product



Measures



OPTIC DIFFUSER:



FINISHED




Technical Data


Input range:	220~240Vac 50-60Hz
Power:	75W
Nº of LEDs:	294 chip SMD 2835 NationStar
Power factor:	>0.95
Luminous efficiency:	90 lm/w
LED power:	0,25W
Luminous flux:	6750 lm (BF) 6700 lm (BN) 6600 lm (BC)
Luminous intensity:	2350cd
IP:	IP20
Operating temperature:	-10°C +40°C
Nº of switching:	30.000
Certifications:	CE, RoHS
Energy Efficiency:	A+
Lifespan:	50.000h (L70:B10)
Dimming:	yes, Opcional, Dali, 1-10V
Weight:	3700 gramos

Photometric data


Angle =120°
Luminous Flux =6750 lm
Colour Temperature CCT=5700K (BF)
CRI =>80




Angle =120°
Luminous Flux =6700 lm
Colour Temperature CCT=4000K (BN)
CRI =>80



Angle =120°
Luminous Flux =6600 lm
Colour Temperature CCT =2700K (BC)
CRI =>80



Luminous Intensity Distribution Curve



Driver used
TRIDONIC



ThreeLine
TECHNOLOGY